

TRANSCUBE GLOBAL 132-1,242 US Gallons



The TransCube Global is a transportable, environmentally friendly double-walled fuel storage tank, that offers an efficient solution for on-site fueling and auxiliary supply.

With its fully transportable design and ability to fuel multiple pieces of equipment simultaneously, the TransCube will save you time and double or triple the run times of your equipment.

FEATURES

LOCKABLE EQUIPMENT CABINET

Equipment and ports are secure and spills are contained. Secure hose access enables fueling while cabinet is locked.

CORNER BRACKETS

Liftable by crane and easily stackable: two high full and three high empty.

GALVANIZED FRAME

Strong, durable and secure structure with added protection from bumps and scratches.

DOUBLE WALLED 110% CONTAINMENT

Built-in, weatherproof secondary containment eliminates the need for pans or basins.

REMOVABLE INNER TANK

For routine cleaning, maintenance and inspection.

INTERNAL BAFFLES

Designed to maximize stability when handling the tank full of fuel.

FOUR WAY FORKLIFT POCKETS

Quick and easy manoeuvring and mobility.





IDEAL USES AND APPLICATIONS

ONSITE FUEL SUPPLY

Easily refuel machinery on site when needed and cut back on fuel delivery waiting times.

FUEL TRANSPORT

Meeting multiple worldwide transport regulations, the TransCube can transport fuel safely anywhere you need it.

GENERATOR AND AUXILIARY EQUIPMENT

TransCube fuel tanks have the ability to quickly and efficiently connect to three diesel powered pieces of equipment and refuel equipment via pump at the same time.

MODELS AND CAPABILITIES



05TCG

10TCG

20TCG

30TCG

40TCG

50TCG

Capacity

(Nominal / safe fill (95%))

132/ 125 US Gallons

251/ 238 US Gallons

552/525 US Gallons

787/ 748 US Gallons

999/ 949 US Gallons

1,204/ 1,144 US Gallons

Dimensions

(L x W x H)

45 x 45 x 34 in

45 x 45 x 52 in

90 x 45 x 52 in

90 x 61 x 52 in

91 x 91 x 45 in

91 x 91 x 52 in

Weight

(empty / full)

893 / 1,951 lbs

1,131 / 3,199 lbs

1,830 / 6508 lbs

2,251 / 8,766 lbs

3,417 / 12,024 lbs

3,695 / 13,744 lbs

Design approvals

UL142, CAN/ULC-S601, US DOT, UN-IBC, TRANSPORT CANADA, NFPA30

